

# Intumescent Smoke Seal ●●●●

Intumescent Fire and smoke seals are used for fitting to doors, door frames, and windows, comprising of a plastic holder containing an intumescent brush smoke seal. Once fitted, the plastic facing of the seals can be painted, although the brush must NOT be painted.

Supplied in 1050mm lengths and 10mm or 20mm width, the intumescent smoke seal strip is backed with self-adhesive tape for easy fitting in rebates.





Standard colour for intumescent BRUSH SMOKE SEAL is BROWN

These products have been tested in accordance with BS476 Part 23 (1987). An integrity of up to 69 minutes was achieved. Also tested to European Standard EN1634-1 (2000) for 68 minutes.

- Suitable for fitting to doors, door frames and windows
- Supplied in convenient 1050mm lengths
- 30 min and 60 min seal available
- Supplied in two widths
- Tested to BS and EN standards

*Smoke kills before flame, it is advisable to fit intumescent strip with brush smoke seals.*

Code	Description	Dimensions
IS14/S	60 min Intumescent Smoke Brush Seal BROWN - Single Door Kit	1050 x 10 x 4mm
IS14/S/DD	60 min Intumescent Smoke Brush Seal BROWN - Double Door Kit	1050 x 10 x 4mm
IS24/S	60 min Intumescent Smoke Brush Seal BROWN - Single Door Kit	1050 x 20 x 4mm
IS24/S/DD	60 min Intumescent Smoke Brush Seal BROWN - Double Door Kit	1050 x 20 x 4mm



**Hoyles Electronic Developments Ltd**

T. 01744 886600

F. 01744 886607

E. [sales@hoyles.com](mailto:sales@hoyles.com)

W. [www.hoyles.com](http://www.hoyles.com)