Security Access Fire Safety Accessories Custom Des
--

Double Push Panic Buttons

Manufactured to BS EN50131 these panic buttons provide a modern and neat solution where a double push latching panic

button is required. The PA microswitch is normally closed and will open only when both buttons are pressed.

Then tamper switch is normally closed, if the lid of the unit is removed the tamper switch will go open.

Available in white ABS or black ABS with a stainless steel cover.

Supplied with a reset key

Specification	PAB-W	PAB-S
Tamper Switch	SP 500mA@	SP 500mA@ 15vdc
Contact	15vdc	
PA Switch	SP 500mA@	SP 500mA@ 15vdc
Contact	15vdc	
IPA	N/C going open	N/C going open
Tamper	N/C going open	N/C going open
Material	White ABS	Black ABS &
		Stainless
Dimensions	80 x 62 x 28 mm	80 x 62 x 28 mm
Weight	0.15kg	0.15kg
IP Rating	IP22	IP22
Approvals	UKCA and CE marked, ROHS compliant	




PAB-S



PAB-W

Benefits and Features

- **Double Push Panic Button** •
- End Push
- No Resistors •
- Colour: White or Black and Stainless •
- Dimensions : 84mm x 65mm x 26 mm •
- **Environmental Class: 2** •
- Security Grade 2 •
- Latching
- Materials: ABS / Stainless Steel
- **Enclosure Tamper Switch**



Dimensions (mm)

Hoyles Electronic Developments Ltd Sandwash Close, Rainford, St Helens, WA11 8LY, UK www.hoyles.com sales@hoyles.com + 44 (0) 1744 886600



