| Security | Access | Fire | Safety | Accessories | Custom Design |
|-------------------------------------|----------------|------|--------|-------------|---------------|
| External Mag | gnetic Lock | | | H-EXN | /IL600-GATE-M |
| Specification - H-I | EXML600-GATE-M | | | | |
| Stainless Steel Housing | | | | | |
| 280kg (600lb) holding force | | | | | |
| Dual Voltage 12/24 VDC @ 500/250mA | | | | | |
| Comes complete with 1 metre cable | | | | | |
| Built in surge prote | ection | | | | |
| Surface mount | | | | | |
| Fail safe operation (power to lock) | | | | 4 | 0 |
| +/- 15% operating temperature | | | | 40 | |
| Push off release pin on armature | | | | | 1 |
| Voltage Free Relay Contacts | | | | | |
| Monitored | | | | | |

Features

| External Magnet IP66 | | |
|----------------------|--|--|
| Weatherproof | | |
| Dual Voltage 12V/24V | | |
| | | |

Side or Face Fixing

Armature comes with fixing kit Suitable Brackets/Housings

H-BKEX600ZL (ZL bracket)


Contents


| External Magnet |
|--------------------------|
| Armature Plate |
| EX600GB Fixing Kit |
| Instructions |
| Armature Fixing Template |

Dimensions

2.64kg boxed

1.55kg unboxed





Hoyles Electronic Developments Ltd Sandwash Close, Rainford, St Helens, WA11 8LY, UK www.hoyles.com sales@hoyles.com + 44 (0) 1744 886600



