

Aidalarm

A600F, A600FKITR, A600FKITRD

The AIDALARM meets the growing demand for an emergency signalling system for disabled persons. Everything is provided in the kit to deliver an effective, fully compliant, simple to install and simple to use system. A range of accessories is available, as stainless-steel flush mount or plastic surface mount. In both cases mounting boxes are supplied.

Requires a separate 12vdc PSU minimum of 250mA, see PSU-12/2AB, if battery backup is required see BAT12V3300LA.

How the Aidalarm Works

- The Aidalarm controller should be sited where staff are located who can respond to an emergency call.
- Ceiling pull cord & optional Dado panic strip or call buttons are situated in the toilet or other area where assistance may be required.
- Pulling the cord or pressing the panic strip/call button generates an immediate audible/visual alarm at both the WC and at the control panel. An LED illuminates on the pull cord giving the caller reassurance the call has been placed.
- The call can be silenced by pressing the button on the front of the control panel.
- The audible indicators at the WC will bleep every 5 seconds to re-assure the caller.
- Should the cord be pulled again while in the silenced state, the system will call again.
- Non-attendance will cause the panel to bleep every 40 seconds as a warning.
- The system can only be reset by the Press to Reset button located at or near the point of call.



Features and Benefits

- DDA Compliant
- BS 8300 Compliant
- High Power Piezo Sounder
- 12 vdc Powered
- Audible & Visual Signalling
- Range of Accessories
- Remote Signalling Output
- Manufactured in the UK
- CE and RoHs compliant

DDA Compliant Kit Contents

A600FKITR - Flush Mount Aidalarm c/w S1600-R Ceiling Pull Cord, S1708SL Reset Button, S1778SR over door indicator and buzzer.

A600FKITRD - Flush Mount Aidalarm c/w S1600-R Ceiling Pull Cord, S1708SL Reset Button, S1778SR over door indicator and buzzer, RPD01000 1000mm Panic Strip.

Optional Accessories



S1778SR

S1708S

S0610

Dimensions (mm)

Bespoke Back Box – 164 x 100 x 55mm

