

Exitguard

EX125i

Exitguard EX125i is a local door alarm designed specifically for integration with Grade 2 EN50131 intruder alarm systems, it is the ideal solution for all types of door security issues. Any alarm or fault is communicated to the main intruder alarm system using a fully supervised loop circuit.

An auto sounder reduction feature is incorporated to attenuate the sounder after a preset period to reduce the annoyance caused if the key holder is not immediately available. However, the sounder will restart if the door is opened again.

The Bleep In Off (BIO) function can be enabled to provide a local audible and visual indication when the Exitguard is turned off. This reduces the likelihood of the Exitguard being left turned off. Selectable resistors on the alarm circuits allow for compatibility with key intruder panel manufacturers' systems. Selectable resistor options are (1k + 1k) or (2k2 + 4k7).

Specification	EX125i
Audible Alarm Indication	Yes
Selectable Tones	Yes
Visual Alarm Indication	Yes
Sounder Output @ 1m	108 dB
Supervised Loop Output	Yes
Supervised Loop Alarm Output	Yes
Keyswitch Control	Yes
Unit Tamper	Yes
Compatibility	All Key Intruder Panels
Dimensions	175 x 125 x 60 mm
Replacement Key Barrels	Yes
Protective Cage Available for use in Harsh Environments	Yes
Country of Manufacture	United Kingdom

Benefits and Features

- Designed for grade 2 intruder systems
- High Power Piezo Sounder 108dB @1m
- Selectable Alarm Tones
- Visual Alarm Indication
- Keyswitch Control with random key numbers
- Audible / visual warning when turned off (BIO)
- FSL On / off monitor output
- Safe Set
- Tamper Switch
- FSL Alarm Output
- Selectable resistor values for outputs
- Simple Function Change by Internal Jumpers
- Compatible with key panel manufacturers

All Exitguards are supplied with fixings, door contact, 1 metre of cable and a door warning sign.



Dimensions (mm)

