Slim Profile, Germ-free Automatic Door Activation Switch

J-Wave

The architrave style, low profile design facilitates a tidy installation on door frames or guiderails. J-Wave's touchless design reduces the spread of germs and improves accessibility in healthcare, retail and commercial settings. With a detection distance of up to 30cm and an ability to detect very fast hand movements in front of the switch body. J-Wave is made from a tough, polycarbonate material with a constantly illuminated LED so that the J-Wave can be easily located in dimly lit environments.

Specification	PRODUCT CODE
IP Rating	54
Detection Method	Active Infrared
Detection Range	10-30cm ± 3-5cm
Power Supply	12-30 VDC 12-24 VAC
Power Consumption	Less than 1.5 W
Relay Output Relay	1A/30VDC
Contact	
Relay Hold Time	1s-2s Pulse Mode
Operating Temperature	-20°C to +50°C
Dimensions	H 117mm x W 40mm x D
	19.5mm

- Slim Design
 Jamb style, low profile design facilitates a tidy installation on door frames or guiderails.
- Eliminate Contamination
 Touchless design reduces the spread of germs
 and improves accessibility in healthcare, retail
 and commercial settings.
- Fast Reaction Time
 Detection distance of up to 30cm with an ability
 to detect very fast hand movements in front of
 the switch body.
 Tough & Illuminated
 Made from a tough, polycarbonate material with

a constantly illuminatedLED so that the J-Wave can be easily located in dimly lit environments.

Detection Range







