

Electronic Locking Magnet Range



FIRE TESTED


The ML600 range of magnets and brackets have been fire tested to BSEN1634-1-2014

(30 & 60 minute timber door-sets)

Slimline Magnetic Lock (600lb)

Technical specifications

- Aluminium housing.
- 12/24 VDC @480/240mA.
- 280kgs (600lb) holding force.
- Built in surge protection.
- ML600-M = Monitored



FEATURES

- Slim line mini magnet.
- Clean and compact design in aluminium.
- Single LED indication on ML600
- Multi LED indication on ML600-M
- No residual magnetism

Suitable brackets:

- BK600ZL (ZL Bracket)
- BK600L (L Bracket)
- AH600 (Armature Housing)

ML600 / ML600-M	250x42x25 (mm)	Magnetic Lock 600lb / 280kg	1.97Kg (Boxed) / 1.13Kg (Unboxed)
Armature	180x35x10 (mm)	Metal armature plate	664g (Unboxed)
BK600ZL	Z = 180L (mm)	ZL Bracket	644g (Boxed) / 556g (Unboxed)
BK600L	L = 251L (mm)	L Bracket	188g (Unboxed)



Hoyles Electronic Developments Ltd

T. 01744 886600 F. 01744 886607 E. sales@hoyles.com W. www.hoyles.com

