

## Aidalarm Press to Reset c/w LED &amp; Sounder

S1708A

Wall mounting Press to Reset button with Braille text plus 2 yellow LEDs and sounder for caller reassurance. Enclosed in white ABS plastic, complete with a single gang surface mounting box. Flush fitting is also possible with a standard single gang back box.

This is a non-latching unit with N.O. contacts specifically designed for use with our Aidalarm Disabled Toilet Alarm systems. The LEDs and sounder have separate terminals. The LED and sounder current limit resistor is provided for 12 vdc operation. The button contacts are rated at 50ma 24vdc resistive, N.O. press to close.

***They should NOT be used for switch feeds to door strikes or mag locks etc.***

Specification	S1708A
Led Current	15A@12vdc
Sounder Current	20m@12vdc
Switch Contacts	50mA@12vdc
Visual Indication	2 x High brightness yellow LED's
Integral Sounder Level	70db @10cm
Tamper	N/A
Material	White ABS
Dimensions	87 x 87 x 36 mm
Weight	0.13kg
IP Rating	IP44 – To maintain the IP rating a suitable sealant or gasket for the rear is required
Approvals	UKCA and CE marked, ROHS compliant

#### Benefits and Features

- ABS back box supplied for surface mount
- Can be semi flush mount onto single gang galvanised back box (not supplied)
- Mark resistant decal
- Tactile button
- Two high brightness yellow LEDs
- Integral sounder

#### Dimensions (mm)

