Security	Access	Fire	Safety	Accessories	Custom Design
Door Status I	ndicator with LED	S			S1717PRG
				manuting bay. Fight bigh	huishteese LEDe


A wall mounted Door status indicator in white ABS complete with a single gang mounting box. Eight high brightness LEDs, four red and four green. Ideal for use with our door interlock systems INTERGUARD. The LED current limit resistor is provided for 12 vdc operation.

Specification	S1717PRG		
Led Current	40mA @12vdc		
Sounder Current	N/A		
Switch Contacts	N/A		
Visual Indication	8 x High Brightness LED's 4 x		
	red, 4 x green		
Integral Sounder Level	N/A		
Tamper	N/A		
Material	White ABS		
Dimensions	87 x 87 x 36mm		
Weight	0.12kg		
IP Rating	IP44 - To maintain the IP		
	rating a suitable sealant or		
	gasket for the rear of the		
	plate is required		
Approvals	UKCA and CE marked, ROHS		
	compliant		

Benefits and Features

- ABS back box supplied for surface mount
- Can be semi flush mount onto single gang galvanised back box (not supplied)
- Mark resistant decal
- Eight high brightness LEDs

Dimensions (mm)





Hoyles Electronic Developments Ltd Sandwash Close, Rainford, St Helens, WA11 8LY, UK www.hoyles.com sales@hoyles.com + 44 (0) 1744 886600



