Security	Access	Fire	Safety	Accessories	Custom Design
Interguard N	laintenance Keys	witch			S1719S

Wall Mounting Stainless Steel two position keyswitch. Designed for use with Interguard door interlock systems as the maintenance switch.

Specifically designed for use with our range of Interguard door interlock controllers.


Specification	S1719S		
Led Current	N/A		
Switch Contacts	DPCO 2A@ 30vdc		
Visual Indication	N/A		
Integral Sounder Level	N/A		
Tamper	N/A		
Material	316 Grade Stainless Steel		
Dimensions	86mm x 86mm x 2mm (Facia)		
	38mm galvanised back box		
Weight	0.28kg		
IP Rating	IP54 - To maintain the IP		
	rating a suitable sealant or		
	gasket for the rear of the		
	plate is required		
Approvals	UKCA and CE marked, ROHS		
	compliant		

Benefits and Features

- Brushed Stainless Steel
- Supplied with 38mm deep galvanised mounting box for flush fitting
- IP Rated
- Customised versions available on request
- Surface mount using \$0610



Dimensions (mm)



Hoyles Electronic Developments Ltd Sandwash Close, Rainford, St Helens, WA11 8LY, UK www.hoyles.com sales@hoyles.com + 44 (0) 1744 886600



