Security	Access	Fire	Safety	Accessories	Custom Design

Keyswitch with Two LEDs – Trapped in ON

Flush fitting stainless steel engraved two position keyswitch with one red and one green flat LED in chrome bezels. This is a double pole unit with change over contacts.

The keyswitch on this version is trapped in the 1 position. Separate terminals are provided for the LED's. The LED current limit resistor is provided for 12 vdc operation.

Specification	S1729ST1		
Led Current	20mA per LED@12vdc		
Switch Contacts	DPCO 2A@ 30vdc		
Visual Indication	2 LED's 1 x red 1x green		
Integral Sounder Level	N/A		
Tamper	N/A		
Material	316 Grade Stainless Steel		
Dimensions	86mm x 86mm x 2mm (Facia)		
	38mm galvanised back box		
Weight	0.28kg		
IP Rating	IP54 - To maintain the IP		
	rating a suitable sealant or		
	gasket for the rear of the		
	plate is required		
Approvals	UKCA and CE marked, ROHS		
	compliant		

Benefits and Features


- Brushed Stainless Steel
- Supplied with 38mm deep galvanised mounting box for flush fitting

S1729ST1

- IP Rated
- Customised versions available on request
- Surface mount using \$0610



Dimensions (mm)



Hoyles Electronic Developments Ltd Sandwash Close, Rainford, St Helens, WA11 8LY, UK www.hoyles.com sales@hoyles.com + 44 (0) 1744 886600



