Fire

Access

A wall mounted High Power Overdoor Light/Sounder unit. There are separate drive inputs for both the light and the sounder. Housed in a low profile single gang ABS enclosure with a scratch resistant decal. Four adjustable tones giving a sounder output at 12vdc up to 108db. LEDs are linked to sounder and strobe in sympathy. Ultra bright LED's available in Red, Green or Yellow. 12 vdc operation.

Specification	S1788P
Led Current	70mA @12vdc
Sounder Current	180mA @12vdc
Switch Contacts	N/A
Visual Indication	8 x High brightness LED's –
	Red, Green or Yellow
Integral Sounder Level	108dB @1m
Tamper	N/A
Material	White ABS
Dimensions	87 x 87 x 36mm
Weight	0.12kg
IP Rating	IP44 - To maintain the IP
	rating a suitable sealant or
	gasket for the rear of the
	plate is required
Approvals	UKCA and CE marked,
	ROHS compliant
Available as:	
S1788PR	8 way indicator with Red
	LED's and sounder
S1788PG	8 way indicator with
	Green LED's and sounder
S1788PY	8 way indicator with
	Yellow LED's and sounder

Benefits and Features

- ABS back box supplied for surface mount
- Can be semi flush mount onto single gang galvanised back box (not supplied)
- Mark resistant decal
- Eight high brightness LEDs
- Intergral Sounder

Dimensions (mm)







