

Mains Rated Relay Kit

S361-MK, S361-MK-24

This kit is designed for switching a 240vac mains load of up to 5A operated by a 12vdc or 24vdc input from an intruder or fire alarm system depending on version.

Two white plastic single gang enclosures are provided for segregation of the alarm system and the mains connections. The first enclosure is tampered and contains a relay with single pole change over contacts.

The relay coil requires 12vdc or 24vdc, depending on version, to operate. An LED is also provided which illuminates when the relay is energised. The tamper switch is normally closed and opens when the face plate is removed from the wall.

The second enclosure is purely a junction box which provides a replication of the SPCO contacts. An earth terminal is also provided for convenient termination of an in coming mains cable.

As the enclosures are all plastic, no earth connection is required. A loop of cable is provided within the kit to connect the two enclosures together.

Specification	S361-MK, S361-MK-24
Switch Contacts	SPCO contacts rated at 5A
Visual Indication	Yes
Integral Sounder Level	N/A
Supply Voltage	S361MK Requires 12vdc supply@60mA S361MK-24 Requires 24vdc supply@60mA
Tamper	Yes
Material	ABS Enclosure PCB module
Supply Input Current	60mA
Single Box Dimensions	87 x 87 x 36mm
Weight	0.290kg
IP Rating	N/A
Approvals	UKCA and CE marked, ROHS compliant Made In UK

